## **HellermannTyton**

## **Specification Sheet**

Part Number: 181-15300



Solid Wall Wiring Duct, 1.5" X 3", Non-Adhesive, PVC, Gray, 120ft/Carton

Article Number	181-15300
Туре	SD1.5X3
Color	Gray (GY)
Features & Benefits	• Solid wall construction provides excellent coverage to keep wires clean. • Durable material protects wires from damage, with long-lasting performance. • A temporary film is applied to the covers to protect against scratches and is writable for identification during installation. • Available standard colors complement or contrast in light and dark environments. • Optional covers snap on and off easily, and are provided with a non-slip lining that insures the covers remain in place during vibration. • Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placement (Covers to be purchased separately.)
Quantity Per	carton

Product Description	HellermannTyton's Pro-Duct, Solid Wall wiring duct efficiently routes and protects wire. Solid Wall wiring duct it designed for straight wire runs where break outs are not required. Pro-Duct, Solid Wall wiring duct is manufactured from high impact, rigid PVC, comes in standard colors of white, gray and black, and is available in 6-foot lengths.
Short Description	Solid Wall Wiring Duct, 1.5" X 3", Non-Adhesive, PVC, Gray, 120ft/Carton
Global Part Name	SD1.5X3-PVC-GY
Technical Description	Non-Adhesive
Length L (Imperial)	6.0
Length L (Metric)	1.83
Width W (Imperial)	1.5
Width W (Metric)	38.1
Height H (Imperial)	3.07
Height H (Metric)	77.90
Mounting Hole Centers (Imperial)	4.0

Material	Polyvinylchloride (PVC)
Material Shortcut	PVC
Flammability	Self-Extinguishing

Halogen free	No
Operating Temperature (Metric)	+122°F (+50°C)
Reach Complaint(Article 33)	No
ROHS Complaint	Yes
Certification/Specification WEB	EN 50085-2-3_1A UL CSA EN 50085-1:2005 + A1:2013
UL Recognized (US)	Yes
Package Quantity(Imperial)	120
Package Quantity (Metric)	36.58
Customs Number	3925900000

© 2018 HellermannTyton. All rights reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions