




REVISIONS						
REV	ECO	DESCRIPTION	DATE	BY	APPR	
А3	-	RELEASE NEW DWG FORMAT	08/30/13	DRP		









AVAILABLE CONNECTOR COLORS

SCALE: NONE

8/30/13


NOTES: UNLESS OTHERWISE SPECIFIED

MATERIAL:

HOUSING: THERMOPLASTIC **SEAL: SILICONE RUBBER**

- 2. MODIFICATIONS: STRAIN RELIEF END CAP; REDUCED DIA. WIRE SEAL
- 3. SPECIFICATIONS:
 - 3.1 CURRENT RATING: 13 AMPS
 - 3.2 OPERATING TEMPERATURE: -55°C TO +125°C
 - 3.3 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
 - 3.4 INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 25°C.
 - 3.5 MOISTURE RESISTANCE: IP67 (MATED CONDITION)
 - 3.6 MATING CYCLE DURABILITY: 100 CYCLES
 - 3.7 RoHS COMPLIANT
- 4. MATING PART: AT06-3S* PLUG (* = MODIFICATIONS AND COLORS)
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.
- 6 CONTACT SIZE AND REAR SEAL WIRE RANGE:

CONTACT	MIN. INSUL	MAX. INSUL	TYPICAL
SIZE	O.D.	O.D.	WIRE RANGE
16	1.35 mm (.053 in)	3.05 mm (.120 in)	



PART NUMBER CHART				
COLOR	PART NUMBER			
GREY	AT04-3P-SR02GRY			
BLACK	AT04-3P-SR02BLK			
BLUE	AT04-3P-SR02BLU			
BROWN	AT04-3P-SR02BRN			
GREEN	AT04-3P-SR02GRN			
RED	AT04-3P-SR02RED			
WHITE	AT04-3P-SR02WHT			
YELLOW	AT04-3P-SR02YEL			

SEE PART NUMBER CHART PART NUMBER QUANTITY UNLESS OTHERWISE SPECIFIED SIGNATURES DATE 1) All dimensions are in metric(mm) D.PARKS 1 PL DEC ±0.30 2 PL DEC ±0.15 3 PL DEC ±0.08 Fractions ±1/64 Angles ±1° 3) Note reference = X MATERIAL SPECIFICATIONS: THIS DRAWING IS SUPPLIED FOR INFORMATION ONLY. DESIGN FEATURES, SPECIFICATIONS AND PERFORMANCE DATA PROCESS SPECIFICATIONS SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHT OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO NORMAL MANUFACTURING VARIATIONS.

NEXT ASS'Y:

MATERIALS LIST **Amphenol** Sine Systems - www.amphenol-sine.com 44724 Morley Drive Clinton Township, MI 48036 RECEPTACLE, 3 PIN, AT SERIES, STRAIN RELIEF END CAP, REDUCED DIA. WIRE SEAL B C-AT04-3P-SR02XXX

DESCRIPTION

RECEP, 3 PIN, AT, STRAIN RELIEF, REDUCED DIA WIRE SEAL

AT04-3P-SR02XXX

23

ITEM

SHEET 1 OF 1